

# TYRE-CHANGERS - TRUCKS & HEAVY DUTY

Excellent quality machine capable of handling earth moving wheels.





For truck, bus, agriculture and Earth-moving heavy tyres, professional truck tyre service and high volume shops. Suitable for both tube and tubeless tyres.





Discover on our website!

# **SUPER-AUTOMATIC HEAVY DUTY TRUCK TYRE CHANGER 14" - 46" / 58"**

Hydraulic

movement



Suitable for control console installation

on pivoting arm (optional).



Hydraulic travel movement of operating arm carriage (left-right).

Operating arm and clamping chuck arm facing each other.

Rim center hole clamping range ø 80 - 1200 mm.

Clamping chuck minimum height from ground 315 mm (center).

Wide and low profiled platform eases the loading of heavy wheels.



Watch the video



automatic rotation. Hydraulic

movement

Operating arm automatic tilting and travelling on carriage.





Wheel clamping by fully hydraulic operated jaws.








Hydraulic movement



All motions controlled by console and pedal box.

Emergency safety button on control console, for stopping all functions.













Suitable for remote control installation (optional). Replaces standard cables and enables all functions control by radio transmission.



#### **STANDARD FEATURES**

SIMIDARD I LAIGRES	
Rim clamping range w/o extensions	14" - 46"
Rim clamping range with extensions (optional)	14" - 58"
Max. tyre diameter	2400 mm (94,5")
Max. tyre width	1300 mm (51")
Power supply	400V - 3ph / 2 speed *
Hydraulic pump motor power	1,5 kW
Gearbox motor power	1,85 / 2,5 kW
Operating pressure	140 bar (2031 psi) ±10%
Bead breaker force	36000 N
Net weight	1025 kg
Max. tyre assembly weight	1800 kg
Max_overall dimensions	2210÷2850x1840÷2050x970÷1900

### **STANDARD ACCESSORIES**



- Short bead lifting lever
- Long bead lifting lever, for agriculture tyres
- Mounting clamp for steel rims

## MAIN OPTIONAL ACCESSORIES











